

DEK Roof Mount Air Conditioner

This roof cooling unit, DEK, with a IP54 protection degree, provides cooling, either to one enclosure or to a complete assembly, depending on the cooling requirements and desired energy consumption level. It is placed on top of the enclosure and is perfect when there is not enough space on the door or side panels.

Feature:
IP55 TYPE 4

CE UL 508A Component
Recognized



Item list

Item no.	Description	Material	Height (mm)	Width (mm)	Depth (mm)	Cooling capacity L35L50 (W)	Power supply (V/ph/Hz)
DEK04BTU9	AC roof 410W 230V	Stainless steel	260	259	481	240	230 / 1 / 50-60
DEK04BTUB	AC roof 410W 230V	Galvanized steel	260	259	481	240	230 / 1 / 50-60
DEK08BTU9	AC roof 820W 230V	Stainless steel	339	341	600	680	230 / 1 / 50-60
DEK08BTUB	AC roof 820W 230V	Galvanized steel	339	341	600	680	230 / 1 / 50-60
DEK12BTU9	AC roof 1150W 230V	Stainless steel	415	401	572	900	230 / 1 / 50-60
DEK12BTUB	AC roof 1150W 230V	Galvanized steel	415	401	572	900	230 / 1 / 50-60
DEK15BTU9	AC roof 1550W 230V	Stainless steel	415	401	572	1200	230 / 1 / 50-60
DEK15BTUB	AC roof 1550W 230V	Galvanized steel	415	401	572	1200	230 / 1 / 50-60
DEK20NTU9	AC roof 2050W 460V	Stainless steel	415	401	572	1560	460 / 3 / 60
DEK20NTUB	AC roof 2050W 460V	Galvanized steel	415	401	572	1560	460 / 3 / 60
DEK30NTU9	AC roof 2900W 460V	Stainless steel	496	492	784	2250	460 / 3 / 60
DEK30NTUB	AC roof 2900W 460V	Galvanized steel	496	492	784	2250	460 / 3 / 60
DEK40NTU9	AC roof 3850W 460V	Stainless steel	496	492	784	2870	460 / 3 / 60
DEK40NTUB	AC roof 3850W 460V	Galvanized steel	496	492	784	2870	460 / 3 / 60
DEK20BT09	AC roof 2050W 230V	Stainless steel	415	401	572	1560	230 / 1 / 50-60
DEK20BT0B	AC roof 2050W 230V	Galvanized steel	415	401	572	1560	230 / 1 / 50-60
DEK20LT09	AC roof 2050W 400V	Stainless steel	415	401	572	1560	400 / 3 / 50-60
DEK20LT0B	AC roof 2050W 400V	Galvanized steel	415	401	572	1560	400 / 3 / 50-60
DEK30BT09	AC roof 2900W 230V	Stainless steel	496	492	784	2250	230 / 1 / 50-60
DEK30BT0B	AC roof 2900W 230V	Galvanized steel	496	492	784	2250	230 / 1 / 50-60
DEK30LT09	AC roof 2900W 400V-60	Stainless steel	496	492	784	2250	400 / 3 / 50-60
DEK30LT0B	AC roof 2900W 400V-60	Galvanized steel	496	492	784	2250	400 / 3 / 50-60
DEK40BT09	AC roof 3850W 230V	Stainless steel	496	492	784	2870	230 / 1 / 50-60
DEK40BT0B	AC roof 3850W 230V	Galvanized steel	496	492	784	2870	230 / 1 / 50-60
DEK40LT09	AC roof 3850W 400V-60	Stainless steel	496	492	784	2870	400 / 3 / 50-60
DEK40LT0B	AC roof 3850W 400V-60	Galvanized steel	496	492	784	2870	400 / 3 / 50-60

Technical data

Finish: RAL 7035 for the galvanized steel versions

Temperature limits outside: +20°C to 55°C* | +20°C to 50°C

Temperature limits inside: +20°C to +50°C

Type of connection: 4-pin plug

Pack quantity: 1

Protection: IP54

Material: Stainless steel | Galvanized Steel